



Handrinse basin	Dimension	Weight	Order number
without overflow, with tap platform, underneath glazed, mm	450		
Colors			
00 White Alpin			
Variant			
•	450 x 335 mm	9.800 kilogram	0738450041
×	450 x 335 mm	9.800 kilogram	0738450070
Infobox			
Mandatory in combination with a bottle trap inclusive ex	tended pipe		
Sanitary ceramics with the special WonderGliss surface time to come. When ordering WonderGliss please add a "1" as eleventh		nttractive-looking for a lone	)
Accessory			
Slotted waste for washbasins without overflow	50 mm	0.300 kilogram	005024
Recommended faucets			
Single lever basin mixer S ceramic cartridge, Projection flexible connection hoses 3/8", aerator adjustable, norm spray, recommended operating pressure 3 - 5 bar, with pop-up waste set,	nal		C11010002



## **D-Neo Handrinse basin** # 0738450041 / 0738450070

|< 450 mm >|

Single lever basin mixer S ceramic cartridge, Projection 101 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	B21010002
Single lever basin mixer S ceramic cartridge, projection 95 mm, flexible connection hoses 3/8", normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	A11010001
Single lever basin mixer S ceramic cartridge, projection 95 mm, flexible connection hoses 3/8", normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	A11010002
Single lever basin mixer S ceramic cartridge, projection 111 mm, flexible connection hoses 3/8", aerator adjustable, flow rate 5,0 l/min (3 bar), normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	B31010002
Single lever basin mixer S ceramic cartridge, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	DE1010001
Single lever basin mixer S ceramic cartridge, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	DE1010002
Single lever basin mixer M ceramic cartridge, Projection 109 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	DE1020001
Single lever basin mixer M ceramic cartridge, Projection 109 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	DE1020002
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	DE1011001
Single lever basin mixer S FreshStart ceramic cartridge, in centre position cold water, Projection 94 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	DE1011002



## **D-Neo Handrinse basin** # 0738450041 / 0738450070

|< 450 mm >|

Single lever basin mixer M FreshStart ceramic cartridge, in centre position cold water, Projection 109 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	Single lever basin mixer M FreshStart ceramic cartridge, in centre position cold water, Projection 109 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	DE1021001
	centre position cold water, Projection 109 mm, flexible connection hoses 3/8", aerator adjustable, normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up	DE1021002

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.