



8251 Seracare

Description

UV resistant, solvent based, ready to use surface protection material with excellent penetrating capacity.

Fields of Application

- Water, damp, dust and stain proofing of all types of porous materials such as concrete, cotto, clinker, ceramic, granite ceramic, brick, natural stones, terrazzo etc. and grouts for both indoor and outdoor applications, thanks to its water repellent property.
- Treating cotto and other highly porous tiles before laying with cement adhesives or before grouting leads much easier cleaning of the finished floor.

Properties

- Water and oil repellent.
- Prevents the appearance of efflorescence and staining.
- Brightens up the colors of the materials.
- UV resistant.

Application

- The surfaces to be treated with Seracare Surface Protector must be absolutely dry and cleaned of dust, grease, wax, paint etc.
- Use rubber gloves during application.
- Apply Seracare Surface Protector with a flat soft brush without diluting.
- Application should be uniform, Seracare Surface Protector must never be poured directly onto the surface that will leave patches when dry.
- Leave Seracare Surface Protector to penetrate for a few minutes and remove any excess with a cloth.
- On highly absorbent materials and in outdoor application, apply it in 2 coats to obtain better results. Wait 4-5 hours between the coats.
- For vertical surfaces apply it by spraying.
- Repeat this process in every 2 years by considering the degree of depreciation of the surface. For every repeated application, clean the surface by using appropriate Seracare products.
- After cleaning, rinse the surface with water and leave to dry. After it is dried, apply Seracare Surface Protector.
- Clean the tools and any contaminated surface with paint solvents.

Post-Application Protection & Suggestions

- After application, application tools can be cleaned with paint solvents.
- Before grouting, care should be taken that the product does not contact the joint gaps.
- Do not breathe vapour. Must be applied in well ventilated environments.
- Wear protective clothing when handling.
- Avoid skin and eye contact.
- Flammable. Smoking should be avoided during application. For further information refer to the safety data sheet.

Storage

- Packages should be kept dry and cool at between +5°C and +35°C in moisture free conditions. Avoid direct sunlight. Keep far from heat, sparks and flames.
- Packages should be protected from water, frost and adverse weather conditions.
- Shelf life is maximum 12 months conditional to complying with the above mentioned conditions.

Packaging

- 1 lt plastic bottles.



8251 Seracare

Technical Properties

(at 23°C and 50% RH)

General Data

| | |
|------------|--|
| Appearance | Transparent liquid |
| Shelf Life | 12 months in original sealed packaging |

Application Data

| | |
|-------------------------------|---|
| Application Temperature Range | (+5°C) - (+35°C) |
| Drying Time | 4-5 hours |
| Consumption | 20 - 100 m ² /lt (Depending on the porosity of the surface) |